

Xpar 360-W

Model: PR-8956

RoHS | CE | LED | $\approx 5m$ | IP20 | T_c150°C | T_a40°C | 

XPar 360-W belongs to XPar indoor LED lighting series, with 60 pcs LEDs(WA), with advantage of long service-time, high output efficiency, non-radiation and low power-consumption. This product features very pure white light, fast strobe, very light weight and small sizes. It is ideal for a lot of application such as the TV studio, concert, banquet hall, and so on.

High output, WA, LED



LED Lighting





Scan with your Phone
to view more detail



Barn Door

Optional



3.9Kg 
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
200W@220V
- Light Source
OSRAM 60x3W(39W+21A), 50,000 hrs
- Strobe
Electronic strobe, 0-25 F.P.S
- Dimmer
0-100% linear adjustment
- Colors
White and amber
- Light Angle
Field angle(1/10 Maximum) $\theta_{1/10}$: 32.8°
Beam angle(1/2 Maximum) $\theta_{1/2}$: 15°
Lens angle: 15° (optional 8°, 25°, 45°)
- Control
International DMX512, 3 pins interface
Standard mode 4 channels and extended mode 7 channels
DMX control mode, master-slave mode, stand-alone mode,
test mode
2 Preset memories
- Other Functions
LED board temperature display
Fixture usage time display
Parameters about DMX mode, display setting status,
operation mode can be transmitted by synchronous control
- Physical
Housing: high temperature, ABS+die-casting aluminum,
IP20
Ambient working temperature: -20°C~40°C

- Weight
Net weight: 3.9kg
- Packaging
Standard: carton 495x360x340(mm)
Optional: flight case 1145x545x535(mm), 6 in 1
- Accessories
C clamp, 1 pc
Safety cord, 1 pc
Signal adapter cable, 2 pcs
Power adapter cable, 1 pc
Optional: barndoor 1 set

