



JNR MINI ELLIPSOIDAL 20C/W

■ JNR-8168A/B

JNR ELLIPSOIDAL 20C/W adopts 20W COB LED (cool white/warm white) which features high brightness and stability. It is made of a new type of high temperature strength of cast aluminum casing with nice outlook. The fixture is designed and manufactured strictly following CE standards, complying with international standard DMX512 protocol. It's available independently controlled and linkable with each other for operation. And JNR ELLIPSOIDAL 20C/W is applicable for large-scale live performances, theater, studio, nightclubs and discos.

Specification

- Input Voltage: AC90-260V 50/60Hz
- LED Quantities:
 - JNR-8168A: 20W CITIZEN COB LED(cool white)
 - JNR-8168B: 20W CITIZEN COB LED(warm white)
- Control Signal: DMX512, master-slave and sound activated or auto operation
- Control: Remote controller
- Power Consumption: 26W
- Dimensions: 250(D)*170(W)*110(H)mm
- Packing Dimensions: 360(D)*180(W)*160(H)mm
- Net Weight: 1.12kg
- Gross Weight: 1.50kg

Detail

- 20W CITIZEN COB LED (cool white/warm white), 50,000 hours
- Color Rendering Index(CRI): $R_a \geq 90$
- Optimized high definition optical system for improved photometric performance and field uniformity
- Projector-quality, high contrast aspheric lens
- Glass reflector that removes greater than 90% infrared radiation (heat) and reflects greater than 95% of visible light
- Lens tube interchangeable with filed angles optional for 19°/26°/36°/50°
- Flat and even hard edge spot image
- Smooth manual focus system
- Beam edge continually adjustable hard-to-soft
- Housing made by die-case aluminum
- Thermally insulated knobs and dual aluminum handle for installing
- 3 Metal spot cutting slots
- Glass/Metal gobo slot as optional
- Color frame as optional
- Manual IRIS system as optional
- 0-100% Smooth and precise linear dimmer
- 25T/sec high speed shutter/strobe effect with variable speed
- Preset variable/random strobe and dimming pulse effect
- Remote controller for different operation functions
- External full range power supply
- Noise free conventional cooling with housing
- -35°C ~45°C Max ambient temperature
- IP20
- Portable (mini C-clamp), canopy-mount and track-mount versions as optional

Light Output (FC=LUX × 0.0929)

