






# XRLED 1500-W Framing

Model: PR-8177A

RoHS | CE |  |  WDMX | LED |  5m |  IP<sub>20</sub> | T<sub>c</sub>150°C | T<sub>a</sub>45°C | 

The XRLED 1500-W Framing(PR-8177A) is the most advanced 600W professional LED moving head. In addition to its complete range of spotlight effects, it has an exclusive endless framing system, designed and patented by PR. It is extremely bright, that the white light is close to conventional 1500W discharge lamp.

600W LED, Framing



Scan with your Phone  
to view more detail




Fixed gobos(Ø36.3mm, image Ø23mm)



Rotating gobos(Ø37.5mm, image Ø24mm)



Color wheel



44Kg   
Size(mm)

## Specifications

- Input Voltages  
100-240V AC, 50/60Hz
- Power Consumption  
880W@220V, 930W@100V
- Light Source  
600W white LED(8,000K), 20,000 hrs  
Ra ≥70, R9 ≥90, Ra ≥95 Lamp(optional)
- Strobe  
Electronic strobe, 0.3-25 F.P.S
- Dimmer  
0-100% linear adjustment
- Colors  
CMY linear color mixing with macros  
1 Color wheel: 6 dichroic colors filters plus open  
Half color effect, variable speed rainbow effect  
Stepping/linear color changing is optional  
Linear color temperature adjustment
- CTO  
0-100% linear CTO system
- Gobos  
1 Rotating gobo wheel: 6 replaceable gobos plus open, glass or metal gobos can be fixed  
Bi-directionally rotatable and wheel scrolling at variable speed, indexable  
Shakable at variable speeds  
1 Fixed gobo wheel: 7 replaceable gobos plus open
- Prism  
One 4-facet prism, bi-directionally rotatable at variable speed, indexable
- Frost  
One linear frost filter
- Effect  
1 Replaceable animation wheel, bi-directionally rotatable at variable speed
- Framing  
4 Sets of framing blades  
Endless rotation, graphics at different sizes and shapes, full curtain effect
- Iris  
5-100% linear adjustment with macro
- Focus  
Motorized linear focus
- Head Movement  
Pan 540°, tilt 270° with auto position correction  
Swap and invert functions of pan and tilt
- Light Angle  
6°~56°
- Control  
International DMX512, 5 pins interface  
Short mode 35 channels, standard mode 38 channels and extended mode 54 channels  
Art Net protocol  
Master-slave mode, stand-alone mode, self-test mode
- Other Functions  
Adjustable pan & tilt speed  
Color touch panel display in English, and its brightness and contrast adjustable  
Fixture and lamp usage time display  
Built-in analyzer for easy fault finding, error messages  
Setup options by chargeable battery inside without power connection  
Software version display  
Modular structure easy for maintenance  
Network interface
- DMX512 wireless receiver  
DMX512 wireless transmitter(optional)
- Weight  
Net weight: 44kg
- Packaging  
Standard: carton 870x660x820(mm)  
Optional: flight case 705x500x860(mm)
- Physical  
Housing: composite plastic, IP20  
Ambient working temperature: maximum 45°C
- Accessories  
G clamp, 2 pcs  
5 pins XLR connector, 1 set  
Safety cord, 2 pcs  
Power cord, 1 pc  
Optional: Ω clamp, 2 pcs

