

XRLED 700 Spot

Model: PR-8163

RoHS | CE | WDMX | LED | 1.3m | IP20 | Tc:150°C | Ta:40°C |

This product uses a new innovation 320W white LED light source, which provides a level of brightness more than 700W traditional lamp. It features with wide zoom range 12°~36°, wireless, compact and lightweight, energy saving and environmental. It's ideal for professional locations such as theatre, stage, TV station, concert, etc.

320W LED, spot






Scan with your Phone to view more detail

Fixed gobos(Ø27.8mm, image Ø23mm)



Rotating gobos(Ø27.8mm, image Ø23mm)



24Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
400W@220V
- Light Source
Atria 320W white LED(8,000±500K), >20,000 hrs
- Strobe
Electronic strobe, 0.3-20 F.P.S with macro
- Dimmer
Electronic dimmer 0-100% linear adjustment
- Colors
1 Color wheel: 6 dichroic colors filters plus open
Rainbow effect at variable speed
- Gobos
1 Rotating gobo wheel: 7 interchangeable gobos plus open, glass or metal gobos can be fixed
Bi-directionally rotating and scrolling effects at variable speed
Indexable , shaking effect at variable speed
1 Fixed gobo wheel: 7 interchangeable gobos plus open
Shaking at variable speed and bi-directional scrolling effect
- Prism
One 3-facet prism, bi-directionally rotating at variable speed, indexable
- Frost
One frost filter
- Iris
5-100% linear adjustment with macros
- Focus
Motorized linear focus
- Zoom
Motorized linear zoom
- Head Movement
Pan 540°, tilt 270° with auto position correction
Swap and Invert functions of pan and tilt
- Light Angle
12°~36°
- Control
International DMX512, 5 pins(optional 3 pins) interface
Short mode 15 channels, standard mode 19 channels, and extended mode 23 channels
Master-slave mode, stand-alone mode, self-test mode
- Other Functions
Adjustable pan & tilt speed
LCD display with English language menu
Fixture and lamp usage time display
Software version display
Built-in analyzer for easy fault finding, error messages
Input signal isolating protection
Modular construction for easy maintenance
DMX512 wireless receiver
DMX512 wireless transmitter(optional)
- Physical
Housing: composite plastic, IP20
Ambient working temperature: maximum 40°C
- Weight
Net weight: 24Kg
- Packaging
Standard: carton 660x572x540(mm)
Optional: flight case 600x507x738(mm)
- Accessories
G clamp, 2 pcs
5 pins XLR connector, 1 set
Safety cord, 2 pcs
Power cord, 1 pc
Optional: Ω clamp 2 pcs

