

TANGO Framing

Model: PR-6611

RoHS | CE | LED | 1.5m | IP65 | Tc:150°C | Ta:40°C




TANGO Framing is a new launched outdoor powerful profile fixture, equipped with 620W bright white LED source. With precise control, 8°~56° wide zoom and multi dynamic effects. It's ideal for urban buildings lighting, landscape lighting and other multi-scale of locations.

IP65, LED Framing



Scan with your Phone
to view more detail

Rotating gobos(Ø37.5mm, image Ø26mm)



37.2Kg
Size(mm)

Specifications

- **Input Voltages**
100-240V AC, 50/60Hz
- **Power Consumption**
800W@230V
- **Light Source**
Atria 620W LED white(7,000K), 20,000 hrs
- **Strobe**
Electronic strobe, 0.3-25 F.P.S
- **Dimmer**
0-100% linear adjustment
- **Colors**
2 Color wheel: 12 dichroic color filters plus open
Half color effect, rainbow effect with bi-directional and variable speeds
Stepping/linear color changing
- **CTO**
0-100% linear CTO system
- **Gobo**
1 Rotating gobo wheel: 6 replaceable gobos plus open, glass and metal gobos can be fixed
Bi-directionally rotating, index, shaking at variable speed and bi-directional scrolling effect
- **Prism**
Two prisms(4-facet and 6-facet prisms)
Optional: 3-facet, coloured prism, 4-facet, gradient prism
Bi-directionally rotating at variable speed, indexable
- **Effect**
Dual effect wheel, independent bi-directional rotation at variable speeds
Shaking effect at variable speeds
- **Framing**
4 Framing module continual framing module rotation, 4 framing blades to make full curtain effect
- **Iris**
5-100% linear adjustment with macros
- **Focus**
DMX linear focus
- **Zoom**
DMX linear zoom
- **Light Angle**
8°~56°
- **Control**
International DMX512, 3 pins(optional 5 pins) interface
RDM control protocol
Short mode 26 channels, standard mode 29 channels, extended mode 38 channels
Master-slave mode, stand-alone mode, test mode
- **Other Functions**
Lamp and total hours displayed
Over temperature protection
Fast and convenient software upgrade via DMX512 interface
Input signal isolation
Modular structure for easy maintenance
DMX512 wireless receiver
DMX512 wireless transmitter(optional)
- **Physical**
Housing: high-intensity die-casting aluminum, IP65
Ambient working temperature: 40°C
- **Weight**
Net weight: 37.2kg
- **Packaging**
Standard: carton 760x690x770(mm)
Optional: flight case 650x402x836(mm)
- **Accessories**
G clamp, 2 pcs
Power cord, 1 pc
Safety cord, 2 pcs
Signal adapter cord, 2 pcs

