

XPAR 354

Model: PR-6209A

RoHS | CE | LED | $\approx 1.5m$ | IP67 | $T_c 150^\circ C$ | $T_a 40^\circ C$ | 

XPAR 354 is a new launched exterior par, rating IP67. It's equipped with 54 pcs of 3W LEDs, provides R/G/B/W single color and countless color mixing effects, ideal for multi-scale outdoor stages, buildings, theme parks, etc.



IP67, 54x3W, RGBW



Architectural Lighting



Scan with your Phone
to view more detail



10Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
180W@220V
- Light Source
54x3W LEDs(12R+18G+18B+6W), 50,000 hrs
- Strobe
Electronic strobe, 0.5-33 F.P.S
- Dimmer
0-100% linear adjustment
- Colors
R/G/B/W, optional(R/G/B/Amber, R/G/B/Lime)
- Light Angle
Beam angle(1/2 peak) $\theta_{1/2}$: 9° (optional 7°, 10°, 20°, 40°)
- Control
International DMX512, 3 pins(optional 5 pins) interface
Standard mode 6 channels and extended mode 11 channels
Master-slave mode, test mode
DMX control mode, preset memory and user memory
- Other Functions
LCD panel
DMX channel mode and settings displayed
LCD and inverted display
Display backlight automatically shut off after delay
Parameters like operation mode and etc. transmitted under synchronization
- Physical
Housing: high intensity cast aluminum alloy, IP67
Ambient working temperature: -20°C~40°C
- Weight
Net weight: 10kg

- Packaging
Standard: carton 475x395x380(mm)
Optional: flight case 873x585x395(mm), 4 in 1
- Accessories
C clamp, 1 pc
Signal adapter cord, 2 pcs
Power cord, 1 pc
Safety cord, 1 pc
Optional: transparent cover+seal+screws x6, 1set; barndoor assembly+frost board, 1 set; top hat, 1 set

