





XR 580 BWS

Model: PR-2552

RoHS | CE |  | WDMX | 550W |  18m |  IP20 | T_c120°C | T_a40°C | 


Version: 20250804

XR 580 BWS(Three in One) is a smart and multi-functional(Beam, Spot and Wash) product with many effects . 160mm front lens produces full and solid beam with 130,000lux @20m, longer projecting distance and perfect visual effects. Fast frost produces wash effect; optical system with smaller beam angle but wider zoom range.




3 in 1, 550W



Fixed gobos



Rotating gobos(Ø22.5mm, image Ø12mm)



26Kg
Size(mm)

Specifications

- Input Voltages
100-240V AC, 50/60Hz
- Power Consumption
800W@220V
Power factor>0.9
- Light Source
PHILIPS MSD Platinum 500L Flex (550W)
(7800K,1500hrs/4000hrs@Energy Save)
- Colors
CMY color mixing system with macros
1 Color wheel: 12colors+ Open,
rainbow effect with bi-directional and variable speeds
Stepping/linear color changing
- CTO
Linear CTO system (0-100%)
- Gobos
1 Fixed gobo wheel: 17 gobos +Open
Bi-directionally rotatable, and shakable at variable speeds
1 Rotating gobo wheel: 7 Interchangeable Gobos +Open
Bi-directionally rotatable, and shakable at variable speeds
- Prism
3 overlapping prisms
(9 facet circular prism)(8 facet circular prism+4 facet linear prism) and some other optional prisms
- Effect
1 graphic effect wheel, bi-directional rotation with variable speeds, and overlapping fixed and rotating gobo wheels
- Frost
1Pc frost filter
- Focus
DMX linear focus
- Zoom
DMX linear focus
- Dimmer/Strobe
0-100% Linearly adjustable/ Double shutter blades
0.3~25 F.P.S
- Head Movement
Pan 540°, Tilt 270° with auto position correction
- Light Angle
Beam Mode: 0°- 2.0°
Spot Mode: 2°- 40° Linear Adjustment
Wash Mode: 3°- 50° Linear Adjustment
- Control
DMX512, 5 pin interfaces (Optional 3-pin)
25channels in short mode, 31channels in standard mode
35channels in extended mode
Self-test mode
- Other Functions
Adjustable Pan & Tilt speeds
Lamp's and fixture's hours displayed
Modular Structure for easy maintenance
DMX512 wireless receiver
DMX512 Wireless Transmitter(Optional)
ArtNet and sACN(Optional)
- Housing
High temperature ABS, IP20
- Ambient temperature
Temperature at maximum 40°C
- Weight
Net weight: 26Kg

- Packaging
Standard: carton 770x730x654(mm)
Optional: flight case 602x549x760(mm)
- Accessories
G clamp, 2 pcs
XLR connector, 1 set(Male and female)
Safety cord, 1 pc
User manual, 0 Pc
Optional: Ω clamp, 2 pcs
- Light Output

